

LabHEAT[®] metal-cased heating mantles series KM-MPE

for operating temperatures up to 450°C

- for <u>three different sizes</u> of glass flasks (Multi size)
- flexible glass yarn heating element an even heat transfer and a gentle treatment of the glassware
- plastic-coated metal housing characterised by a chemical-resistant metal housing providing excellent stability
- high quality design made by hand work
- thermally insulated and earthed
- predrilled threaded hole on rear allows to fix the clamp KM-SK (accessories)
- with built-in heating zone switches
- with built-in controller allows a continous adjustment of power outlet
- with residual current detection (RCD)
- ٠CE

our heating mantles perform the requirements based on the european harmonized standards





Technical specification

KM-MPE

Nominal voltage	230 V AC	
Nominal power	see ordering details	
Heating zones	see ordering details	
Safety class	1	
Sytem of protection	casing IP 43, heating surface IP 00	
Heating element temperature	max. 450°C	
Power supply cable	1,5 m with schuko-plug (earthed) and RCD switch	

Heating-zone selection

2

2/3

1/3

З

1/1

Switch position
3 heating zones
Power



3 heating zones = 3 flask sizes

Ordering details

Volume ml / l	Flask Ø mm	Power W	Heating zones	Dimensions Ø x H mm	PartNo.
50 - 250	51 - 85	160	3	175 x 180	93000250
250 - 1000	85 - 131	350	3	220 x 190	93001000
1 - 3	131 - 185	700	3	300 x 220	93003000

We also manufacture special heating mantles with other specifications - available on request

Accessories

Support clamp type KM-SK

Part.-No. 97000001

to fix support rods with diameter up to \emptyset 13 mm

We supply a full range of controllers and temperature regulators.

SAF Wärmetechnik GmbH Weinheimer Str. 2a D-69509 Mörlenbach Tel. + 49 (0) 6209 797 96-0 Fax + 49 (0) 6209 797 96-29 E-Mail: info@saf-gmbh.de Internet: www.saf-gmbh.de